


Olhal Fêmea (802)



8.8



Medida	A	B	C	E	F	H	Peso	Código
	mm						Kg	
M6	25	45	25	10	10	45	0,100	309.080506
M8	25	45	25	10	10	45	0,100	309.080508
M10	25	45	25	10	10	45	0,100	309.080510
M12	35	63	35	14	14	62	0,260	309.080512
M14	35	63	35	14	14	62	0,260	309.080514
M16	35	63	35	14	14	62	0,260	309.080516
M18	50	90	50	20	20	90	0,750	309.080518
M20	50	90	50	20	20	90	0,750	309.080520
M24	50	90	50	20	20	90	0,750	309.080524
M27	60	108	65	24	24	109	1,400	309.080527
M30	60	108	65	24	24	109	1,400	309.080530

Cargas de Trabalho W.L.L. (Ton)

Medida	     						Máx.Força Aperto (Nm)
	0°	0°	0°-45°	45°-60°	0°-45°	45°-60°	
	1 Perna	2 Pernas	2 Pernas		3 e 4 Pernas		
M6	0,4	0,8	0,14	0,1	0,2	0,14	3,5
M8	0,8	1,6	0,28	0,2	0,4	0,28	8
M10	1	2	0,35	0,25	0,5	0,35	16
M12	1,6	3,2	0,56	0,4	0,8	0,56	28
M14	3	6	1	0,75	1,5	1	45
M16	4	8	1,4	1	2	1,4	70
M18	5	10	1,8	1,25	2,5	1,8	95
M20	6	12	2,1	1,5	3	2,1	135
M24	8	16	2,8	2	4	2,8	230
M27	10	20	3,5	2,5	5	3,5	343
M30	12	24	4,2	3	6	4,2	465

Coeficiente de segurança: 4

Para ser aparafusado à mão

Coefficiente de segurança: 4

Para ser aparafusado à mão