


OLHAL DE SOLDAR



Coeficiente de segurança 4.

Medida	W.L.L	A	B	C	D	E	F	I	Peso	Código
	Ton	mm							Kg	
01	1,12	35	41	36	13	28	66	40	0,39	309.03601
02	2	38	42	39	13	33	74	44	0,51	309.03602
03	3,15	42	45	43	17	34	80	49	0,70	309.03603
05	5,3	60	55	50	22	44	95	55	1,50	309.03605
08	8	70	70	65	26	53	108	70	2,60	309.03608
15	15	90	97	90	34	73	155	92	5,85	309.03615

Cargas de Trabalho W.L.L. (Ton)

Medida	         									
	0°	0°	90°	90°	0°-45°	45°-60°	Asymm	0°-45°	45°-60°	Asymm
	1 Perna	2 Pernas	1 Perna	2 Pernas	2 Pernas			3 e 4 Pernas		
01	1,12	2,24	1,12	2,24	1,57	1,12	1,12	2,35	1,68	1,12
02	2	4	2	4	2,8	2	2	4,2	3	2
03	3,15	6,3	3,15	6,3	4,41	3,15	3,15	6,62	4,73	3,15
05	5,3	10,6	5,3	10,6	7,42	5,3	5,3	11,13	7,95	5,3
08	8	16	8	16	11,2	8	8	16,8	12	8
15	15	30	15	30	21	15	15	31,5	22,5	15