


Olhais de Suspensão Forjados

DIN 582 Material C 15



Refª	Dimensões (mm)							S.W.L. (kg)			Força Máx. Aperto Nm	Peso (kg)	Código
	A	B	C	E	F	G	H	Vertical	45°	90°			
M 6	20	36	20	8,5	8	10	36	90	60	45	3,5	0,060	309.01006
M 8	20	36	20	8,5	8	10	36	140	100	70	8	0,060	309.01008
M 10	25	45	25	10	10	12	45	230	170	115	16	0,100	309.01010
M 12	30	54	30	11	12	14	53	340	240	170	28	0,170	309.01012
M 14	30	54	30	11	12	14	53	500	350	250	45	0,150	309.01014
M 16	35	63	35	13	14	16	62	700	500	350	70	0,260	309.01016
M 18	35	63	35	13	14	16	62	930	650	465	95	0,240	309.01018
M 20	40	72	40	16	16	19	71	1200	860	600	135	0,410	309.01020
M 22	40	72	40	16	16	19	71	1500	1050	750	182	0,360	309.01022
M 24	50	90	50	20	20	24	90	1800	1290	900	230	0,750	309.01024
M 27	54	98	62	22	22	26	99	2500	1830	1250	343	0,800	309.01027
M 30	60	108	65	25	24	28	109	3200	2300	1600	465	1,400	309.01030
M 33	60	108	65	25	24	28	109	4200	3050	2100	632	1,270	309.01033
M 36	70	126	75	30	28	32	128	4600	3300	2300	814	2,030	309.01036
M 39	80	144	85	35	32	38	147	6000	4400	3000	1059	3,200	309.01039
M 42	80	144	85	35	32	38	147	6300	4500	3150	1304	3,050	309.01042
M 45	90	166	100	40	38	46	168	7800	5500	3900	1638	5,000	309.01045
M 48	90	166	100	40	38	46	168	8600	6100	4300	1981	4,820	309.01048
M 52	100	184	110	45	42	50	187	9900	7100	4950	2540	7,000	309.01052
M 56	100	184	110	45	42	50	187	11500	8200	5750	3000	6,690	309.01056